









	Alimentazione Power supply	2 x 1,5V LR6/AA size Alkaline
	Durata batterie mesi Battery life, months	12
	Contatto in deviazione SPDT Contacts rating	8A 250Vac (cosφ1) 2A 250Vac (cosφ0,6)
	Regolazione COMFORT COMFORT temperature range	+6 +30°C
	Regolazione NOTTURNA NIGHT-TIMETemperature	+6 +30°C
	Differenziale Temperature differential	0,3 °C
No.	Classe di isolamento Insulation class	
	Grado di protezione IP IP index of protection	IP30
	Modello con orologio giornaliero Daily program model	RTC10
	Modello con orologio settimanale Weekly program model	RTC20

USESThe RTC series microprocessor-controlled chronothermostats allow heating or cooling control according to your own lifestyle requirements. The RTC series chronothermostats have been designed to work with all energy sources (gas, heating oil, electricity). Dual electronic microprocessor-controlled thermostat. Switching contacts. PROGRAMMING Traditional knobs for independently adjusting comfort and reduced temperature settings. Segmented analogical clock with lock-in time band pointers. BATTERY-POWERED. Two-lead connection: can replace any previous model of room thermostat without having to change the electric plant. Wall-mounting or built-in on most common mounting-boxes for electric plants. Visual battery discharge warning.

## Four posistions switch for selecting mode:

- SET TEMPERATURE using the timer switch
- COMFORT temperature, constant
- REDUCED temperature, constant
- ANTIFREEZE temperature.

S.p.A. VIA GRA